


MIRO 6.2 OPTO-COUPLER MODULE

IN: 30 VDC - OUT: 48 VDC / 0,1 A / 500kHz

Transistor 0.1 A
24 V DC
Switching frequency: max. 500 kHz
Spring clamp terminals

[Link til artikel](#)

Billede



Produktet kan afvige fra billedet



Commercial data	
ECLASS-6.0	27371604
ECLASS-6.1	27371604
ECLASS-7.0	27371604
ECLASS-8.0	27371604
ECLASS-9.0	27371604
ECLASS-10.1	27371604

ECLASS-11.1	27371604
ECLASS-12.0	27371604
ETIM-5.0	EC001504
customs tariff number	85414900
GTIN	4048879024372
Pakke-enhed	1
Electrical data Input	
Input voltage OFF DC min.	0 V
Input voltage OFF DC max.	7 V
Input voltage DC min.	10 V
Input voltage DC max.	30 V
Current input DC	5,5 mA
Electrical data Output	
Switch off delay max.	0,1 µs
Quiescent current OFF max.	0,25 mA
Switching frequency ohmic max.	500000 Hz
Voltage switching DC min.	5 V
Switching voltage DC max.	48 V
Switching current min.	0 mA
Switching current max.	0,1 A
Voltage drop AC max.	1,2 V
Voltage drop DC max.	1,2 V
Diagnostics	
Status indication LED	yellow
Device protection Electrical	
Rated insulation voltage	2750 V
Device protection Media	
Flame resistance	flame retardant
Mechanical data Material data	
Color housing	black
Material housing	Plastic
Mechanical data Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	91 mm
Width	6,2 mm
Depth	70 mm
Environmental characteristics Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	60 °C