

**MODLINK MSDD DATA INSERT**

1×USB-A fem./fem. + 1×RJ45 + 2×PS2 fem./sold.

USB (form A); RJ45; PS2; PS2  
 1× RJ45, 8-pole metal, CAT5e (female/female)  
 1× USB 3.0 (female/female) form A  
 2× PS2 (6-pole solder connection)

**[Link til artikel](#)****Billede**

Produktet kan afvige fra billedet

**Commercial data**

ECLASS-6.0	27189217
ECLASS-6.1	27189217
ECLASS-7.0	27189217
ECLASS-8.0	27189217
ECLASS-9.0	27189217
ECLASS-10.1	27182806
ECLASS-11.1	27182806
ECLASS-12.0	27182806
ETIM-5.0	EC002625
customs tariff number	85366990
GTIN	4048879037457
Pakke-enhed	1

**Mechanical data | Mounting data**

Height	88 mm
Width	51 mm
Depth	70,4 mm

**Environmental characteristics | Climatic**

Storage temperature min.	5 °C
Storage temperature max.	40 °C

**Shielding plate**

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 25.06.2024

Murrelektronik ApS | Alexander Foss Gade 13, 1. | 9000 Aalborg | Fon +45 96 35 06 06 | Fax | shop@murrelektronik.dk | shop.murrelektronik.dk

Connection information	Threaded hole M4
Tightening torque	0,9 Nm
<b>USB</b>	
Operating voltage AC	48 V
Operating voltage DC	48 V
Operating voltage AC max. (UL-listed)	30 V
Operating voltage DC max. (UL-listed)	42,4 V
Operating current	1,5 A
USB specification	3.0
Data transmission rate max.	5000 MBit/s
Looking techniques	Snap-in connector
<b>RJ45</b>	
Operating voltage AC max. (UL-listed)	30 V
Operating voltage DC max. (UL-listed)	42,4 V
Current operating max. (UL)	175 mA
Family construction form	RJ45
Family type Back side	RJ45
Cable category min.	Cat5e
Looking techniques	Snap-in connector
<b>PS2</b>	
Connection cross section max.	0,5 mm <sup>2</sup>
AWG number max.	20
Operating voltage AC	30 V
Operating voltage DC	30 V
Operating current	1 A
Family construction form	PS2
Family type Back side	PS2
Gender	female
Gender Rear	Lötanschluss
Looking techniques	Screw locking
No. of poles	6