


**SIEMENS CONTACTOR SUPPRESSOR**

Diode and LED, 24VDC

24 V DC  
Diode + LED  
For other configurations and voltages, please inquire.

[Link to Product](#)

Illustration



Product may differ from Image



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27371013 |
| ECLASS-6.1      | 27371013 |
| ECLASS-7.0      | 27371013 |
| ECLASS-8.0      | 27371013 |
| ECLASS-9.0      | 27371013 |
| ECLASS-10.1     | 27371013 |

|                                                 |                                  |
|-------------------------------------------------|----------------------------------|
| ECLASS-11.1                                     | 27371013                         |
| ECLASS-12.0                                     | 27371013                         |
| ETIM-5.0                                        | EC002498                         |
| customs tariff number                           | 85363010                         |
| GTIN                                            | 4048879017480                    |
| Packaging unit                                  | 1                                |
| <b>Compatibility   Compatible with</b>          |                                  |
| Appropriate contactors                          | 3 TH 2; 3 TF 2; 3 TH 20; 3 TF 20 |
| <b>Electrical data</b>                          |                                  |
| Damping factor                                  | 1.5× UN                          |
| <b>Electrical data   Input</b>                  |                                  |
| Input voltage DC min.                           | 12 V                             |
| Input voltage DC max.                           | 30 V                             |
| <b>Installation   Connection</b>                |                                  |
| Connection information                          | self-securing cable forks        |
| <b>Device protection   Media</b>                |                                  |
| Flame resistance                                | flame retardant                  |
| <b>Mechanical data   Material data</b>          |                                  |
| Combustibility class housing (UL94)             | V-0                              |
| Material housing                                | Plastic                          |
| <b>Mechanical data   Mounting data</b>          |                                  |
| Height                                          | 19,5 mm                          |
| Width                                           | 20 mm                            |
| Depth                                           | 24,5 mm                          |
| <b>Environmental characteristics   Climatic</b> |                                  |
| Operating temperature min.                      | -20 °C                           |
| Operating temperature max.                      | 70 °C                            |