MURR ELEKTRONIK
stay connected

MSVD POWER SOCKET NEMA (GFCI)


Mounting rail

USA (2× NEMA-GFCI 5-20)
(Ground Fault Circuit Interrupter)
Screw terminals
Each socket can be loaded with 20 A, however, the total load of both sockets must be below 30 A.

Link to Product

Illustration





Product may differ from Image

Commercial data	
ECLASS-6.0	27189217
ECLASS-6.1	27142305
ECLASS-7.0	27142305
ECLASS-8.0	27142305
ECLASS-9.0	27142305
ECLASS-10.1	27142305
ECLASS-11.1	27142305
ECLASS-12.0	27142305
ETIM-5.0	EC000020
customs tariff number	85366990
GTIN	4048879041386
Packaging unit	1

Electrical data	
Fault current min.	4 mA
Fault current max.	6 mA

Electrical data | Supply	
Operating voltage AC	125 V
Operating current max.	20 A

Installation	
Connection cross section max.	6 mm²

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28

Installation | Connection	
Connection	Screw terminals SK
Mechanical data | Mounting data	
Mounting method	geschnappt
Suitable for mounting type	mounting rail, (EN 60715)
Height	126 mm
Width	64 mm
Depth	55 mm

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-03-28