

SCREW PLUG M12 STAINLESS STEEL

6-edges, 14 mm

Screw plug M12×1 mm  
Metal, hex, 1 piece  
Stainless steel 1.4305 (V2A)

Link to Product

Illustration



Product may differ from Image

| Commercial data                          |                                       |
|------------------------------------------|---------------------------------------|
| ECLASS-6.0                               | 23111190                              |
| ECLASS-6.1                               | 23111190                              |
| ECLASS-7.0                               | 23111190                              |
| ECLASS-8.0                               | 23111190                              |
| ECLASS-9.0                               | 23111190                              |
| ECLASS-10.1                              | 23111190                              |
| ECLASS-11.1                              | 23111102                              |
| ECLASS-12.0                              | 23111102                              |
| ETIM-5.0                                 | EC000032                              |
| customs tariff number                    | 73269098                              |
| GTIN                                     | 4048879333764                         |
| Packaging unit                           | 1                                     |
| Installation   Connection                |                                       |
| Tightening torque                        | 0,6 Nm                                |
| Mounting set                             | M12 x 1                               |
| Device protection   Electrical           |                                       |
| Degree of protection (EN IEC 60529)      | IP65, IP67, IP68                      |
| Degree of protection (ISO 20653:2013)    | IP66K, IP69K                          |
| Additional condition protection degree   | inserted, screwed                     |
| Mechanical data   Material data          |                                       |
| Material housing                         | Stainless steel 1.4305 (V2A)          |
| Mechanical data   Mounting data          |                                       |
| Mounting method                          | inserted, screwed, Shaking protection |
| Environmental characteristics   Climatic |                                       |
| Operating temperature min.               | -100 °C                               |

Operating temperature max. 205 °C