

**MODLINK MSDD DATA INSERT**

1×SUB-D9 fem./male + 1×RJ45 + 1×USB-A fem./fem.

RJ45; USB (A); SUB-D9  
1× RJ45, 8-pole metal, CAT5e (female/female)  
1× USB 3.0 (female/female) form A  
1× SUB-D9 (female/male)

**Link to Product**

**Illustration**



Product may differ from Image



**Commercial data**

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27189217      |
| ECLASS-6.1            | 27189217      |
| ECLASS-7.0            | 27189217      |
| ECLASS-8.0            | 27189217      |
| ECLASS-9.0            | 27189217      |
| ECLASS-10.1           | 27182806      |
| ECLASS-11.1           | 27182806      |
| ECLASS-12.0           | 27182806      |
| ETIM-5.0              | EC002625      |
| customs tariff number | 85366990      |
| GTIN                  | 4048879037549 |
| Packaging unit        | 1             |

**Mechanical data | Mounting data**

|        |         |
|--------|---------|
| Height | 88 mm   |
| Width  | 51 mm   |
| Depth  | 70,4 mm |

**Environmental characteristics | Climatic**

|                          |       |
|--------------------------|-------|
| Storage temperature min. | 5 °C  |
| Storage temperature max. | 40 °C |

**Shielding plate**

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Connection information                | Threaded hole M4                               |
| Tightening torque                     | 0,9 Nm                                         |
| <b>USB</b>                            |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 1,5 A                                          |
| USB specification                     | 3.0                                            |
| Data transmission rate max.           | 5000 MBit/s                                    |
| Looking techniques                    | Snap-in connector                              |
| <b>SUB-D9</b>                         |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D9                                         |
| Family type Back side                 | SUB-D9                                         |
| Gender                                | female                                         |
| Gender Rear                           | male                                           |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 9                                              |
| <b>RJ45</b>                           |                                                |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | RJ45                                           |
| Family type Back side                 | RJ45                                           |
| Cable category min.                   | Cat5e                                          |
| Looking techniques                    | Snap-in connector                              |