

SIGNAL TOWER MODLIGHT30 EQUIPPED WITH LED MODULES

Green, amber, red with 4 pole M12 connection

Connection module + LED modules green, yellow, red with M12 connection Connection cables are in the online shop under "Connection Technology".

Link to Product





Product may differ from Image



Commercial data	
ECLASS-6.0	27371230
ECLASS-6.1	27371230
ECLASS-7.0	27371230
ECLASS-8.0	27371230
ECLASS-9.0	27371230
ECLASS-10.1	27371230
ECLASS-11.1	27371230
ECLASS-12.0	27371230
ETIM-5.0	EC001042
customs tariff number	85318070
GTIN	4048879496896
Packaging unit	1
Electrical data Supply	
Operating voltage AC	24 V
Operating voltage DC	24 V
Current consumption max.	85 mA
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP65
Mechanical data Material data	
Color housing	black
mation in this Product-PDE has been compiled with	the utmost care

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-06

Murrelektronik ApS | Alexander Foss Gade 13, 1. | 9000 Aalborg | Fon +45 96 35 06 06 | Fax | shop@murrelektronik.dk | shop.murrelektronik.dk



Material housing	Plastic	
Mechanical data Mounting data		
Height	30 mm	
Width	30 mm	
Depth	213 mm	
Environmental characteristics Cli	matic	
Operating temperature min.	-20 °C	
Operating temperature max.	60 °C	
Connection type 1		
Family construction form	M12	
Gender	male	
Coding	Α	
No. of poles	4	
PIN 1	GN	
PIN 2	RD	
PIN 3	COM	
PIN 4	YE	

The information in this Product-PDF has been compiled with the utmost care. Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2024-05-06 Murrelektronik ApS | Alexander Foss Gade 13, 1. | 9000 Aalborg | Fon +45 96 35 06 06 | Fax | shop@murrelektronik.dk | shop.murrelektronik.dk