MURR ELEKTRONIK
stay connected

## MIRO TH 24VDC SK OPTO-COUPLER MODULE


IN: 50 VDC - OUT: 250 VAC / 0,5A


Triac 0.5 A
24 V DC
Screw terminals


Link til artikel

### Billede






Produktet kan afvige fra billedet

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27371604 |
| ECLASS-6.1 | 27371604 |
| ECLASS-7.0 | 27371604 |
| ECLASS-8.0 | 27371604 |
| ECLASS-9.0 | 27371604 |
| ECLASS-10.1 | 27371604 |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-11.1 | 27371604 |
| ECLASS-12.0 | 27371604 |
| ETIM-5.0 | EC001504 |
| customs tariff number | 85414900 |
| GTIN | 4048879026789 |
| Pakke-enhed | 1 |
| **Electrical data \| Input** | |
| Input voltage OFF DC min. | 0 V |
| Input voltage OFF DC max. | 5 V |
| Input voltage DC min. | 10 V |
| Input voltage DC max. | 53 V |
| Current input DC | 7 mA |
| **Electrical data \| Output** | |
| Switch off delay max. | 10 ms |
| Switch on delay max. | 10 ms |
| Quiescent current OFF max. | 0,3 mA |
| Additional condition switching frequency | depending on wiring |
| Switching frequency max. | 20 Hz |
| Voltage switching AC min. | 24 V |
| Switching voltage AC max. | 250 V |
| Switching current min. | 1,5 mA |
| Switching current max. | 0,5 A |
| Voltage drop AC max. | 1,5 V |
| **Diagnostics** | |
| Status indication LED | yellow |
| **Device protection \| Electrical** | |
| Rated surge voltage | 2,5 kV |
| **Device protection \| Media** | |
| Flame resistance | flame retardant |
| **Mechanical data \| Material data** | |
| Color housing | black |
| Material housing | Plastic |
| **Mechanical data \| Mounting data** | |
| Mounting method | geschnappt |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height | 78 mm |
| Width | 6,2 mm |
| Depth | 70 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C |
| **Connection type 4** | |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | black |
| No. of poles | 1 |
| PIN 1 | 13 |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

| | |
|---|---|
| Color contact carrier | black |
| No. of poles | 1 |
| PIN 1 | 14 |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | black |
| No. of poles | 1 |
| PIN 1 | A 1 |
| Connection | Screw terminals SK |
| Family construction form | terminal |
| Gender | female |
| Color contact carrier | black |
| No. of poles | 1 |
| PIN 1 | A 2 |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024