


LUGS 16 FOR SIGNAL TRANSFER

250V / 8 A

16-pole  
Screw plug-in terminals

[Link til artikel](#)

Billede



Produktet kan afvige fra billedet

| Commercial data       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27143424      |
| ECLASS-6.1            | 27260708      |
| ECLASS-7.0            | 27141152      |
| ECLASS-8.0            | 27141152      |
| ECLASS-9.0            | 27141152      |
| ECLASS-10.1           | 27141152      |
| ECLASS-11.1           | 27141152      |
| ECLASS-12.0           | 27141152      |
| ETIM-5.0              | EC001283      |
| customs tariff number | 85369010      |
| GTIN                  | 4048879026284 |
| Pakke-enhed           | 1             |

**Electrical data | Supply**

|                        |       |
|------------------------|-------|
| Operating voltage AC   | 250 V |
| Operating current max. | 8 A   |

**Installation**

|                                     |                   |
|-------------------------------------|-------------------|
| Connection cross-section solid max. | 4 mm <sup>2</sup> |
|-------------------------------------|-------------------|

**Installation | Connection**

|            |                    |
|------------|--------------------|
| Connection | Screw terminals SK |
|------------|--------------------|

**Device protection | Electrical**

|                                   |   |
|-----------------------------------|---|
| Overvoltage category (EN 60664-1) | I |
|-----------------------------------|---|

**Mechanical data | Mounting data**

|                            |                           |
|----------------------------|---------------------------|
| Mounting method            | geschnappt                |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height                     | 75 mm                     |
| Width                      | 45 mm                     |
| Depth                      | 66 mm                     |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C  |