

IMPACT67 COMPACT MODULE, PLASTIC

CANopen, 16 dig Out

Digital outputs

DO16 - 0.5 A

CAN 1 Mbit/s; M12, A-coded

7/8", 5-pole, 2x max. 9 A

M12, 5-pole, A-coded


Connection cables are in the online shop under "Connection Technology".

Housing fully potted.

mounting compatible with I/O modules of the MVK series

[Link til artikel](#)

Billede



Produktet kan afvige fra billedet



Classifications

ECLASS-6.0	27242604
ECLASS-6.1	27242604
ECLASS-7.0	27242604
ECLASS-8.0	27242604
ECLASS-9.0	27242604
ECLASS-10.1	27242604
ECLASS-11.1	27242604
ECLASS-12.0	27242604
ETIM-5.0	EC001604

Electrical data | Supply

Total current UA max.	9 A
Total current US max.	9 A

Electrical data | Output

Overload resistant	yes
Short-circuit protected	yes
Output current per pin max.	0,5 A

Industrial communication Bus data	
Address range min.	1
Address range max.	99
Industrial communication CANopen	
CANopen addressing	Rotary switch
Diagnostics	
Diagnostic	No voltage, Under voltage
Diagnostic via BUS	per module and channel
Diagnostic via LED	per module and channel
LED display	Ethernet connection/data traffic
Device protection Electrical	
Degree of protection (EN IEC 60529)	IP67
Mechanical data Mounting data	
Suitable for mounting type	2-hole screw mounting
Height	39 mm
Width	63 mm
Depth	225 mm
Environmental characteristics Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	70 °C
Storage temperature min.	-25 °C
Storage temperature max.	70 °C
Connection types	
Connection type 1	0-7
Connection type 2	Bus In
Connection type 3	Bus Out
Connection type 4	Power In
Connection type 5	Power Out
Connection type 1	
Family construction form	M12
Gender	female
Color contact carrier	gray
Coding	A
No. of poles	5
Connection type 2	
Family construction form	M12
Gender	male
Color contact carrier	black
Coding	A
No. of poles	5
Connection type 3	
Family construction form	M12
Gender	female
Color contact carrier	black
Coding	A
No. of poles	5
Connection type 4	
Family construction form	7/8"
Gender	male
Color contact carrier	black

No. of poles	5
--------------	---

Connection type 5

Family construction form	7/8"
--------------------------	------

Gender	female
--------	--------

Color contact carrier	black
-----------------------	-------

No. of poles	5
--------------	---

Commercial data

customs tariff number	85389099
-----------------------	----------

GTIN	4048879052009
------	---------------

Pakke-enhed	1
-------------	---