MURR ELEKTRONIK
stay connected

**Emergency stop with 2 positive opening**


contacts in a IP65 enclosure


E-Stop 42 2NC L M12(8)
with M12 connection
8-pole
Emergency-Stop button
2 NC (positively-opening)
LED-Ring can be lit
mounting with clip on the back side


[Link til artikel]

**Billede**






Produktet kan afvige fra billedet

**Commercial data**

| | |
|---|---|
| ECLASS-6.0 | 27371244 |
| ECLASS-6.1 | 27371244 |
| ECLASS-7.0 | 27371244 |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-8.0 | 27371244 |
| ECLASS-9.0 | 27371244 |
| ECLASS-10.1 | 27371244 |
| ECLASS-11.1 | 27371244 |
| ECLASS-12.0 | 27371244 |
| ETIM-5.0 | EC002034 |
| customs tariff number | 85365080 |
| GTIN | 4048879594219 |
| Pakke-enhed | 1 |
| **Electrical data** | |
| Operating voltage AC/DC LED illumination max. | 30 V |
| Operating current LED illumination | 4 mA @24 V DC |
| **Electrical data \| Supply** | |
| Operating voltage DC min. | 1 V |
| Operating voltage DC max. | 36 V |
| Operating voltage DC (UL Recognized) | 30 V |
| Operating current | 1,5 A |
| **Device protection** | |
| Condition lifetime | load-dependent, temperature dependent |
| **Device protection \| Electrical** | |
| Degree of protection (EN IEC 60529) | IP65 |
| Electrical lifetime | 50000 Cycles |
| **Device protection \| Mechanical** | |
| Mechanical endurance | 50000 Cycles |
| Operating life B10d | 250000 Cycles |
| **Mechanical data** | |
| Bounce time max. | 10 ms |
| **Mechanical data \| Material data** | |
| Material contact | AgNi |
| **Mechanical data \| Mounting data** | |
| Height | 52 mm |
| Width | 124 mm |
| Depth | 42 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -25 °C |
| Operating temperature max. | 70 °C |
| Storage temperature min. | -25 °C |
| Storage temperature max. | 85 °C |
| **Technical Data \| Reliability** | |
| Lambda normally closed contact | 20 % |
| **Connection type 1** | |
| Family construction form | M12 |
| Gender | male |
| Color contact carrier | black |
| Coding | A |
| No. of poles | 8 |
| PIN 1 | NC 1 |
| PIN 2 | NC 1 + |
| PIN 3 | NC 2 |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

| | |
|---|---|
| PIN 4 | NC 2 + |
| PIN 7 | X 2 - |
| PIN 8 | X 1 + |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024