MURR ELEKTRONIK
stay connected

Illuminated Emergency-stop pushbutton with 2 positive opening contacts


in a IP65 enclosure


E-Stop 72 2NC L M12(8)
with M12 connection
8-pole
Emergency-Stop button
2 NC (positively-opening)
LED-Ring can be lit


Link til artikel

Billede









Produktet kan afvige fra billedet

Commercial data

ECLASS-6.0	27371244
ECLASS-6.1	27371244
ECLASS-7.0	27371244
ECLASS-8.0	27371244

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

MURR ELEKTRONIK
stay connected

ECLASS-9.0	27371244
ECLASS-10.1	27371244
ECLASS-11.1	27371244
ECLASS-12.0	27371244
ETIM-5.0	EC002034
customs tariff number	85365080
GTIN	4048879594813
Pakke-enhed	1
Electrical data	
Operating voltage AC/DC LED illumination min.	12 V
Operating voltage AC/DC LED illumination max.	30 V
Operating current LED illumination	15 mA @24 V AC/DC
Electrical data | Output	
Utilization category AC-15 (EN IEC 60947-5-1)	3 A @ 250 V
Utilization category DC-13 (EN IEC 60947-5-1)	2 A @ 24 V
Switching current (AC-15)	30 A
Switching current (DC-13)	2,2 A
Device protection	
Condition lifetime	load-dependent, temperature dependent
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Electrical lifetime	1000000 Cycles
Device protection | Mechanical	
Mechanical endurance	1000000 Cycles
Operating life B10d	250000 Cycles
Mechanical data	
Bounce time max.	9 ms
Mechanical data | Material data	
Material contact	AgNi
Mechanical data | Mounting data	
Mounting method	screwed
Height	103 mm
Width	72 mm
Depth	91 mm
Environmental characteristics | Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	60 °C
Storage temperature min.	-25 °C
Storage temperature max.	85 °C
Technical Data | Reliability	
Lambda normally closed contact	20 %
Connection type 1	
Family construction form	M12
Gender	male
Color contact carrier	black
Coding	A
No. of poles	8
PIN 1	NC 1

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

PIN 2	NC 1
PIN 3	NC 2
PIN 4	NC 2
PIN 7	X 2 -
PIN 8	X 1 +

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024