MURR ELEKTRONIK
stay connected

## R-Button 30 1NO L M12(4)


Illuminiated reset button

R-Button 30 1NO L M12(4)
Illuminiated reset button
Frontring stainless steel
Mounting hole 30,3 mm
Connection M12 (4-pin)

### Link til artikel

**Billede**






Produktet kan afvige fra billedet

| Commercial data | |
|---|---|
| ECLASS-6.1 | 27371228 |
| ECLASS-7.0 | 27371228 |
| ECLASS-8.0 | 27371228 |
| ECLASS-9.0 | 27371228 |
| ECLASS-10.1 | 27371228 |
| ECLASS-11.1 | 27371228 |
| ECLASS-12.0 | 27371228 |
| customs tariff number | 85365080 |
| GTIN | 4065909019627 |
| Pakke-enhed | 1 |
| **Electrical data \| Supply** | |
| Operating voltage DC min. | 20 V |
| Operating voltage DC max. | 28 V |
| Rated operating voltage AC-15 | 35 V |
| Rated operating voltage DC-13 | 35 V |
| Rated operating current | 0,1 A |
| **Electrical data \| Input** | |
| Short-circuit current | 1000 A |
| **Electrical data \| Output** | |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 28.03.2024

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| Switching power max. | 1 W |
| Voltage switching AC min. | 0,02 V |
| Switching voltage AC max. | 35 V |
| Voltage switching DC min. | 0,02 V |
| Switching voltage DC max. | 35 V |
| Switching voltage DC max. (UL 60947) | 30 V |
| Switching voltage peak DC (UL 60947) | 42,4 V |
| Switching current min. | 0,01 mA |
| Switching current max. | 100 mA |
| **Installation \| Connection** | |
| Family construction form | M12 |
| **Installation \| Pin assignment** | |
| Coding | A |
| No. of poles | 4 |
| **Device protection \| Electrical** | |
| Installation height max. ASL | 2000 m |
| Degree of protection front (EN IEC 60529) | IP66, IP67, IP69 |
| Degree of protection back (EN IEC 60529) | IP66, IP67 |
| Pollution Degree | 2 |
| Rated insulation voltage | 250 V |
| Short circuit protective device (SCPD) | fuse 250 V / 0.1 A / 1.5 kA gG quick |
| Overvoltage category (EN 60950-1) | II |
| **Device protection \| Mechanical** | |
| Mechanical endurance | 500000 Cycles |
| Mechanical endurance B10 | 650000 Cycles |
| UL enclosure type rating front side | type 4X |
| **Device protection \| Media** | |
| Salt-spray resistance (IEC 60068-2-11) | yes |
| **Mechanical data** | |
| Can be illuminated | yes |
| Actuating function | spring return |
| Actuating force min. | 5 N |
| Actuating force max. | 12 N |
| Actuating travel max. | 1 mm |
| Color | black |
| Color collar | black |
| Color front ring | black |
| Color illuminant | white |
| Shape collar | round |
| Contact type | 1 S |
| Type of illuminant | LED |
| **Mechanical data \| Material data** | |
| Material housing | Plastic |
| Material contact | Gold |
| **Mechanical data \| Mounting data** | |
| Mounting method | Threaded ring |
| Installation height | 3,9 mm |
| Mounting depth | 36,4 mm |
| Mounting hole | 30,3 mm |
| Height | 34,5 mm |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 28.03.2024

| | |
|---|---|
| Width | 40 mm |
| Grid min. | 35 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -25 °C |
| Operating temperature max. | 70 °C |
| Derating from | 40 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | 85 °C |
| Relative humidity max. (operation) | 93 % |
| **Connection type 1** | |
| Family construction form | M12 |
| Gender | male |
| Color contact carrier | black |
| Coding | A |
| No. of poles | 4 |
| PIN 1 | NO |
| PIN 2 | LED (A) |
| PIN 3 | LED (K) |
| PIN 4 | NO |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 28.03.2024