MURR ELEKTRONIK
stay connected

LED-INDICATOR OPAC / GREEN


LED-24V IP65

(green)
24 V AC/DC
The modules are suitable for wall thickness of 1.5...5.0 mm.

[Link til artikel]

Billede





Produktet kan afvige fra billedet

Commercial data

ECLASS-6.0	27261590
ECLASS-6.1	27261501
ECLASS-7.0	27261501
ECLASS-8.0	27261501
ECLASS-9.0	27261501
ECLASS-10.1	27261501
ECLASS-11.1	27261501
ECLASS-12.0	27261501
ETIM-5.0	EC000272
customs tariff number	85318070
GTIN	4048879041270
Pakke-enhed	10

Electrical data | Supply

Operating voltage AC	24 V
Operating voltage AC min.	20,4 V
Operating voltage AC max.	26,4 V
Operating voltage DC	24 V
Operating voltage DC min.	20,4 V
Operating voltage DC max.	26,4 V
Current consumption min.	8 mA
Current consumption max.	12 mA

Installation | Connection

Connection information	Faston 2.8×0.8 mm

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

Device protection | Media	
Flame resistance	flame retardant
Mechanical data	
Diameter LED	5 mm
Mechanical data | Material data	
Material housing	Plastic
Mechanical data | Mounting data	
Diameter front panel drilling	9 mm
Environmental characteristics | Climatic	
Operating temperature min.	-20 °C
Operating temperature max.	50 °C

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024