


MEN POWER SUPPLY 1/2-PHASE, SMOOTHED

IN: 115/230+/-10VAC OUT: :24V/7,5ADC

Current: 7.5 A  
Output rating: 180 W  
without DIN-rail adapter  
This power supply units meet the (EN 61000-3-2) standard for harmonic current.  
For any mounting position at vertical wall.

[Link til artikel](#)

Billede



Produktet kan afvige fra billedet

| Commercial data       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27049002      |
| ECLASS-7.0            | 27049002      |
| ECLASS-8.0            | 27049002      |
| ECLASS-9.0            | 27040701      |
| ETIM-5.0              | EC002540      |
| customs tariff number | 85044095      |
| GTIN                  | 4048879079969 |
| Pakke-enhed           | 1             |
| Electrical data       |               |

Security level SELV

**Electrical data | Supply**

Power frequency 50 ... 60 Hz

**Electrical data | Input**

|                                         |                 |
|-----------------------------------------|-----------------|
| Fuse protection 1 primary side external | 3 A @115 V AC   |
| Fuse protection 2 primary side external | 1,5 A @230 V AC |
| Characteristic back-up fuse             | Inertia         |
| Input voltage 1 AC                      | 115 V           |
| Input voltage 1 AC min.                 | 105 V           |
| Input voltage 1 AC max.                 | 125 V           |
| Input voltage 2 AC                      | 230 V           |
| Input voltage 2 AC min.                 | 220 V           |
| Input voltage 2 AC max.                 | 240 V           |
| Input current at input voltage 1 AC     | 2,84 A          |
| Input current at input voltage 2 AC     | 1,42 A          |

**Electrical data | Output**

|                                         |                               |
|-----------------------------------------|-------------------------------|
| Fuse protection secondary side external | 15 A                          |
| Output suppression                      | LED, Screening capacitor, VDR |
| Output voltage DC                       | 24 V                          |
| Output voltage adjustable               | no                            |
| Output current max.                     | 9 A                           |
| Type of secondary fuse                  | Flat fuse FKS                 |
| Ripple max.                             | 5 %                           |

**Mechanical data | Mounting data**

|                            |                         |
|----------------------------|-------------------------|
| Suitable for mounting type | Schlüssellochaufhängung |
| Mounting dimension a       | 86,5 mm                 |
| Mounting dimension b       | 90 mm                   |
| Mounting dimension c       | 5,8 mm                  |
| Height                     | 103 mm                  |
| Width                      | 105 mm                  |
| Depth                      | 150,5 mm                |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -20 °C |
| Operating temperature max. | 60 °C  |
| Derating from              | 40 °C  |

**Conformity**

|                  |                                   |
|------------------|-----------------------------------|
| Product standard | EN 61558-2-6, EN 62041 category I |
| EMC              | EN 55011 B, EN 61000-3-2          |

**Connection type 3**

|                          |                    |
|--------------------------|--------------------|
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | metallic           |
| No. of poles             | 1                  |
| PIN 1                    | PE                 |
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | green              |
| No. of poles             | 3                  |
| PIN 1                    | +                  |

|                          |                    |
|--------------------------|--------------------|
| PIN 2                    | -                  |
| PIN 3                    | -                  |
| Connection               | Screw terminals SK |
| Family construction form | terminal           |
| Gender                   | female             |
| Color contact carrier    | green              |
| No. of poles             | 5                  |
| PIN 1                    | + 10 V             |
| PIN 3                    | - 10 V             |
| PIN 4                    | 115 V              |
| PIN 5                    | 230 V              |