

EUROCARD HOLDER

SKPD form D, 230V, 32-pole, 234x160mm

screw terminal

32-pole

230 V AC

To insert the card first press down the 2 yellow buttons. Then slide the Eurocard into the guide slots pushing until fully engaged. The card is now locked into position. It can be removed by pressing down on the 2 yellow buttons.

[Link til artikel](#)

Billede



Produktet kan afvige fra billedet



Commercial data

ECLASS-6.0	27260710
ECLASS-6.1	27260704
ECLASS-7.0	27440402
ECLASS-8.0	27440402
ECLASS-9.0	27440402
ECLASS-10.1	27440402
ECLASS-11.1	27460201
ECLASS-12.0	27460201
ETIM-5.0	EC002780
customs tariff number	85366990
GTIN	4048879040051
Pakke-enhed	1

Electrical data | Supply

Operating voltage AC	230 V
Operating current max.	4 A

Installation

Connection cross-section solid min.	0,25 mm ²
Connection cross-section solid max.	4 mm ²
Connection cross-section stranded/fine-stranded min.	0,5 mm ²

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 10.05.2024

Murrelektronik ApS | Alexander Foss Gade 13, 1. | 9000 Aalborg | Fon +45 96 35 06 06 | Fax | shop@murrelektronik.dk | shop.murrelektronik.dk

Connection cross-section stranded/fine-stranded max. 2,5 mm²

Installation | Connection

Connection Screw terminals SK

Installation | Pin assignment

No. of poles 32

Device protection | Media

Flame resistance flame retardant

Mechanical data | Material data

Material housing Plastic

Mechanical data | Mounting data

Mounting method screwed

Suitable for mounting type mounting rail

Height 63 mm

Width 274 mm

Depth 167 mm