

**MIRO 6.2 PLUGGABLE COMPL.MODULE OUTPUT RELAY**

IN: 6 VAC/DC - OUT: 250 VAC/DC / 6 A

[Link til artikel](#)

| Commercial data                               |                                          |
|-----------------------------------------------|------------------------------------------|
| ECLASS-6.0                                    | 27371601                                 |
| ECLASS-6.1                                    | 27371601                                 |
| ECLASS-7.0                                    | 27371601                                 |
| ECLASS-8.0                                    | 27371601                                 |
| ECLASS-9.0                                    | 27371601                                 |
| ECLASS-10.1                                   | 27371601                                 |
| ECLASS-11.1                                   | 27371601                                 |
| ECLASS-12.0                                   | 27371601                                 |
| ETIM-5.0                                      | EC001437                                 |
| customs tariff number                         | 85364900                                 |
| GTIN                                          | 4048879021333                            |
| Pakke-enhed                                   | 1                                        |
| Electrical data   Input                       |                                          |
| Input voltage DC                              | 6 V                                      |
| Input voltage DC min.                         | 5 V                                      |
| Input voltage DC max.                         | 7,2 V                                    |
| Input current                                 | 25 mA                                    |
| Electrical data   Output                      |                                          |
| Utilization category AC-12 (EN IEC 60947-5-1) | 6 A @ 24, 6 A @ 110 V, 6 A @ 230 V       |
| Utilization category AC-15 (EN IEC 60947-5-1) | 3 A @ 24 V, 3 A @ 110 V, 1,5 A @ 230 V   |
| Utilization category DC-13 (EN IEC 60947-5-1) | 1 A @ 24 V, 0,2 A @ 110 V, 0,1 A @ 230 V |
| Switching frequency max.                      | 10 Hz                                    |
| Power rating AC max.                          | 1500 VA                                  |
| Power rating DC max.                          | 180 W                                    |
| Switching voltage AC max.                     | 250 V                                    |
| Switching voltage DC max.                     | 30 V                                     |
| Switching current DC                          | 100 mA                                   |
| Switching current max.                        | 6 A                                      |
| Diagnostics                                   |                                          |
| Status indication LED                         | green                                    |
| Device protection                             |                                          |
| Condition lifetime                            | load-dependent                           |
| Device protection   Electrical                |                                          |
| Degree of protection (EN IEC 60529)           | IP20                                     |
| Electrical lifetime NC                        | 10000 Cycles                             |
| Electrical lifetime NO                        | 30000 Cycles                             |
| Device protection   Mechanical                |                                          |
| Mechanical endurance                          | 10000000 Cycles                          |
| Mechanical data                               |                                          |
| Drop-out time max.                            | 4 ms                                     |
| Response time max.                            | 8 ms                                     |
| Mechanical data   Material data               |                                          |
| Material contact                              | Ag Sn O2                                 |
| Mechanical data   Mounting data               |                                          |

|                            |                           |
|----------------------------|---------------------------|
| Mounting method            | geschnappt                |
| Suitable for mounting type | mounting rail, (EN 60715) |
| Height                     | 93 mm                     |
| Width                      | 6,2 mm                    |
| Depth                      | 75,6 mm                   |

**Environmental characteristics | Climatic**

|                            |        |
|----------------------------|--------|
| Operating temperature min. | -25 °C |
| Operating temperature max. | 60 °C  |

**Connection type 5**

|                          |                           |
|--------------------------|---------------------------|
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | 12                        |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | 11                        |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | 14                        |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | A 1                       |
| Connection               | Spring clamp terminals FK |
| Family construction form | terminal                  |
| Gender                   | female                    |
| Color contact carrier    | black                     |
| No. of poles             | 1                         |
| PIN 1                    | A 2                       |