

MODLINK MSDD DATA INSERT

1×SUB-D9 fem./male + 1×RJ45 + 1×USB-A fem./fem.

- RJ45; USB (A); SUB-D9
- 1× RJ45, 8-pole metal, CAT5e (female/female)
  - 1× USB 3.0 (female/female) form A
  - 1× SUB-D9 (female/male)

Link til artikel

Billede



Produktet kan afvige fra billedet



| Commercial data                          |               |
|------------------------------------------|---------------|
| ECLASS-6.0                               | 27189217      |
| ECLASS-6.1                               | 27189217      |
| ECLASS-7.0                               | 27189217      |
| ECLASS-8.0                               | 27189217      |
| ECLASS-9.0                               | 27189217      |
| ECLASS-10.1                              | 27182806      |
| ECLASS-11.1                              | 27182806      |
| ECLASS-12.0                              | 27182806      |
| ETIM-5.0                                 | EC002625      |
| customs tariff number                    | 85366990      |
| GTIN                                     | 4048879037549 |
| Pakke-enhed                              | 1             |
| Mechanical data   Mounting data          |               |
| Height                                   | 88 mm         |
| Width                                    | 51 mm         |
| Depth                                    | 70,4 mm       |
| Environmental characteristics   Climatic |               |
| Storage temperature min.                 | 5 °C          |
| Storage temperature max.                 | 40 °C         |
| Shielding plate                          |               |

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Connection information                | Threaded hole M4                               |
| Tightening torque                     | 0,9 Nm                                         |
| <b>USB</b>                            |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 1,5 A                                          |
| USB specification                     | 3.0                                            |
| Data transmission rate max.           | 5000 MBit/s                                    |
| Looking techniques                    | Snap-in connector                              |
| <b>SUB-D9</b>                         |                                                |
| Operating voltage AC                  | 48 V                                           |
| Operating voltage DC                  | 48 V                                           |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Operating current                     | 3 A                                            |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | SUB-D9                                         |
| Family type Back side                 | SUB-D9                                         |
| Gender                                | female                                         |
| Gender Rear                           | male                                           |
| Looking techniques                    | Standard UNC 4-40 screw thread bolt (EN 60807) |
| No. of poles                          | 9                                              |
| <b>RJ45</b>                           |                                                |
| Operating voltage AC max. (UL-listed) | 30 V                                           |
| Operating voltage DC max. (UL-listed) | 42,4 V                                         |
| Current operating max. (UL)           | 175 mA                                         |
| Family construction form              | RJ45                                           |
| Family type Back side                 | RJ45                                           |
| Cable category min.                   | Cat5e                                          |
| Looking techniques                    | Snap-in connector                              |