MURR ELEKTRONIK
stay connected

**Bus terminating plug M12 female B-cod.**


Termination resistor, Profibus


PROFIBUS
Terminating resistor
Female
M12, 4-pole
B-coded


## Link til artikel

### Billede






Produktet kan afvige fra billedet

### Side 1

| | |
|---|---|
| Family construction form | M12 |
| Degree of protection (EN IEC 60529) | IP67 |

### Commercial data

| | |
|---|---|
| ECLASS-6.0 | 27061801 |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024

MURR ELEKTRONIK
stay connected

| | |
|---|---|
| ECLASS-6.1 | 27260702 |
| ECLASS-7.0 | 27440390 |
| ECLASS-8.0 | 27440190 |
| ECLASS-9.0 | 27440190 |
| ECLASS-10.1 | 27440190 |
| ECLASS-11.1 | 27440190 |
| ECLASS-12.0 | 27440190 |
| ETIM-5.0 | EC001855 |
| customs tariff number | 85331000 |
| GTIN | 4048879419123 |
| Pakke-enhed | 1 |
| **Electrical data \| Supply** | |
| Operating voltage DC max. | 30 V |
| Operating voltage DC max. (UL-listed) | 30 V |
| Current operating per contact max. | 4 A |
| **Installation \| Connection** | |
| Tightening torque | 0,6 Nm |
| **Device protection \| Electrical** | |
| Additional condition protection degree | inserted, screwed |
| **Mechanical data \| Material data** | |
| Coating locking | Nickeled |
| Locking material | Zinc die-casting |
| **Mechanical data \| Mounting data** | |
| Mounting method | inserted, screwed, Shaking protection |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -25 °C |
| Operating temperature max. | 85 °C |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 29.03.2024