

M8 panel feed through male / female 0° A-cod.

4-pol., shielded

Control cabinet entry system

Male - female




M8, 4-pole


Rear mounting

shielded

[Link til artikel](#)

Billede





Produktet kan afvige fra billedet

Side 1

Family construction form	M8
Material contact	Copper alloy
No. of poles	4

Commercial data

ECLASS-6.0	27143423
ECLASS-7.0	27449001
ECLASS-8.0	27449001
ECLASS-9.0	27440321
ECLASS-10.1	27440109
ECLASS-11.1	27440109
ECLASS-12.0	27440109
ETIM-5.0	EC002640
customs tariff number	85366990
GTIN	4048879689304
Pakke-enhed	1

Electrical data | Supply

Operating voltage DC	60 V
Current operating per contact max.	4 A

Diagnostics

Status indication LED	no
-----------------------	----

Installation | Connection

Mating cycles min.	100
--------------------	-----

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP67
Additional condition protection degree	inserted, screwed
Pollution Degree	3
Rated surge voltage	1,5 kV
Overvoltage category (EN 60950-1)	II

Mechanical data

Contour for corrugated hose	without
-----------------------------	---------

Mechanical data | Material data

Coating contact	gold plated
Material housing	Metal
Material contact carrier	PA

Mounting method	inserted, screwed
-----------------	-------------------

Operating temperature min.	-25 °C
Operating temperature max.	85 °C