

**M8 male 0° / M8 female 0° A-cod. shielded**

PVC 3x0.34 shielded bk UL/CSA 2.7m

Male straight – female straight


M8 – M8, 3-pole



shielded

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link til artikel](#)**Billede**



Produktet kan afvige fra billedet



|                                        |                         |
|----------------------------------------|-------------------------|
| Cable length                           | 2,7 m                   |
| Side 1                                 |                         |
| Tightening torque                      | 0,4 Nm                  |
| Family construction form               | M8                      |
| Thread                                 | M8 x 1                  |
| Width across flats                     | SW9                     |
| Side 2                                 |                         |
| Tightening torque                      | 0,4 Nm                  |
| Thread                                 | M8 x 1                  |
| Commercial data                        |                         |
| ECLASS-6.0                             | 27279218                |
| ECLASS-6.1                             | 27279218                |
| ECLASS-7.0                             | 27279218                |
| ECLASS-8.0                             | 27279218                |
| ECLASS-9.0                             | 27060311                |
| ECLASS-10.1                            | 27060311                |
| ECLASS-11.1                            | 27060311                |
| ECLASS-12.0                            | 27060311                |
| ETIM-5.0                               | EC001855                |
| customs tariff number                  | 85444290                |
| GTIN                                   | 4048879624480           |
| Pakke-enhed                            | 1                       |
| Electrical data   Supply               |                         |
| Operating voltage AC max.              | 50 V                    |
| Operating voltage DC max.              | 60 V                    |
| Operating voltage AC (UL-listed)       | 30 V                    |
| Operating voltage DC (UL-listed)       | 30 V                    |
| Current operating per contact max.     | 4 A                     |
| Device protection   Electrical         |                         |
| Degree of protection (EN IEC 60529)    | IP65, IP67, IP68, IP66K |
| Additional condition protection degree | inserted, screwed       |

|                                                         |                                                  |
|---------------------------------------------------------|--------------------------------------------------|
| Pollution Degree                                        | 3                                                |
| Rated surge voltage                                     | 1,5 kV                                           |
| Material group (IEC 60664-1)                            | I                                                |
| <b>Mechanical data   Material data</b>                  |                                                  |
| Coating locking                                         | Nickeled                                         |
| Material housing                                        | PUR                                              |
| Locking material                                        | Zinc die-casting                                 |
| <b>Mechanical data   Mounting data</b>                  |                                                  |
| Mounting method                                         | inserted, screwed, Shaking protection            |
| <b>Environmental characteristics   Climatic</b>         |                                                  |
| Operating temperature min.                              | -25 °C                                           |
| Operating temperature max.                              | 85 °C                                            |
| Additional condition temperature range                  | depending on cable quality                       |
| <b>Conformity</b>                                       |                                                  |
| Product standard                                        | DIN EN 61076-2-114 (M8)                          |
| <b>Installation   Cable</b>                             |                                                  |
| Cable identification                                    | 600                                              |
| Cable Type                                              | 1                                                |
| Jacket Color                                            | black                                            |
| Type of Certificate                                     | cURus                                            |
| Amount stranding                                        | 1                                                |
| Stranding                                               | 3 wires twisted                                  |
| Cable shielding (type)                                  | copper braid, tinned                             |
| Cable shielding (coverage)                              | 80 %                                             |
| Banding                                                 | Fleece, Foil                                     |
| wire arrangement                                        | brown, black, blue                               |
| Cable weight                                            | 52,8 g/m                                         |
| Material jacket                                         | PVC                                              |
| Shore hardness jacket                                   | 85 ± 5 Shore A                                   |
| Freedom from ingredients (jacket)                       | lead-free, cadmium-free, CFC-free, silicone-free |
| Outer-diameter (jacket)                                 | 5 mm                                             |
| Tolerance outer diameter (sheath)                       | ± 5 %                                            |
| Material wire insulation                                | PVC                                              |
| Amount wires                                            | 3                                                |
| Outer diameter insulation                               | 1,25 mm                                          |
| Outer diameter tolerance core insulation                | ± 5 %                                            |
| Shore hardness wire insulation                          | 45 ± 5 Shore D                                   |
| Material properties wire insulation                     | good machinability                               |
| Ingredient freeness wire insulation                     | lead-free, cadmium-free, CFC-free, silicone-free |
| Amount strands (wire)                                   | 19                                               |
| Diameter of single wires                                | 0,15 mm                                          |
| Conductor crosssection (wire)                           | 0,34 mm <sup>2</sup>                             |
| Material conductor wire                                 | Stranded copper wire, bare                       |
| Conductor type (wire)                                   | Strand class 5                                   |
| Current load capacity (standard)                        | to DIN VDE 0298-4                                |
| Current load capacity min. wire                         | 6 A                                              |
| Electrical resistance line constant wire                | 57 Ω/km @ 20 °C                                  |
| Nominal voltage power AC max.                           | 300 V                                            |
| AC withstand voltage power (wire - shield)              | 2 kV @ 60 s                                      |
| Power frequency withstand voltage power (wire - jacket) | 2 kV @ 60 s                                      |
| AC withstand voltage power (wire - wire)                | 2 kV @ 60 s                                      |
| Min. operating temperature (static)                     | -30 °C                                           |

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 20.04.2024

Murrelektronik ApS | Alexander Foss Gade 13, 1. | 9000 Aalborg | Fon +45 96 35 06 06 | Fax | shop@murrelektronik.dk | shop.murrelektronik.dk

|                                      |                                                      |
|--------------------------------------|------------------------------------------------------|
| Max. operating temperature (fixed)   | 80 °C                                                |
| Operating temperature min. (dynamic) | -5 °C                                                |
| Operating temperature max. (dynamic) | 80 °C                                                |
| UV resistance                        | DIN EN ISO 4892-2 A                                  |
| Flame resistance                     | IEC 60332-2-2   UL 1581 § 1090   UL 1581 § 1100 FT2  |
| chemical resistance                  | Good, application-related testing                    |
| Gasoline resistance                  | Good, application-related testing                    |
| Oil resistance                       | DIN EN 60811-404   Good, application-related testing |
| Bending radius (fixed)               | 10 x Outer diameter                                  |