

M12 POWER PANEL FEED THROUGH 4-pole S-CODED**M12 POWER PANEL FEED THROUGH 4-pole S-CODED**

Male - female

Front mounting

Fastening nut included in the delivery




good resistance to oil and chemicals




The resistance to aggressive media should be individually tested for your application. Further details on request.

Lead-free without exception (CE - RoHS)


Cap nut

(M16 × 1.5 mm)

[Link til artikel](#)**Billede**



Produktet kan afvige fra billedet



Side 1	
Family construction form	M12P
Coding	S
No. of poles	4
Degree of protection (EN IEC 60529)	IP65, IP67, IP68
Side 2	
Family construction form	M12P
Coding	S
No. of poles	4
Degree of protection (EN IEC 60529)	IP65, IP67, IP68
Commercial data	
ECLASS-6.0	27279220
ECLASS-7.0	27440103
ECLASS-8.0	27440103
ECLASS-9.0	27440103
ECLASS-10.1	27440109
ECLASS-11.1	27440109
ECLASS-12.0	27440109

ETIM-5.0	EC002061
customs tariff number	85366990
GTIN	4065909049952
Pakke-enhed	1
Electrical data Supply	
Operating voltage AC max.	600 V
Current operating per contact max.	12 A
Installation Connection	
Tightening torque	0,6 Nm
Mounting set	M16 x 1.5
Device protection	
Shielded	yes
Device protection Electrical	
Additional condition protection degree	inserted, screwed
Pollution Degree	3
Rated surge voltage	6 kV
Material group (IEC 60664-1)	I
Mechanical data Material data	
Coating housing	nickel plated
Material housing	Brass
Mechanical data Mounting data	
Mounting method	inserted, screwed, Shaking protection
Environmental characteristics Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	85 °C
Important installation notes	
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
Note on bending radius	Attention: Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.
Conformity	
Product standard	IEC 61076-2-111