

**M12 female 90° A-cod. with cable AIDA**

PUR 5x0.34 ye UL/CSA+drag ch. 30m

AIDA conform

Female 90°




M12, 5-pole

Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request


Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Further cable lengths on request.

[Link til artikel](#)**Billede**

Produktet kan afvige fra billedet



Cable length

30 m

**Side 1**

Tightening torque

0,6 Nm

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.

Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 20.05.2024

Murrelektronik ApS | Alexander Foss Gade 13, 1. | 9000 Aalborg | Fon +45 96 35 06 06 | Fax | shop@murrelektronik.dk | shop.murrelektronik.dk

|                                           |                   |
|-------------------------------------------|-------------------|
| Family construction form                  | M12               |
| Thread                                    | M12 x 1           |
| suitable for corrugated tube (internal Ø) | 10 mm             |
| Cable outlet                              | angled            |
| Coding                                    | A                 |
| No. of poles                              | 5                 |
| Width across flats                        | SW13              |
| Degree of protection (EN IEC 60529)       | IP65, IP66K, IP67 |

**Side 2**

|                           |                |
|---------------------------|----------------|
| Stripping length (jacket) | 20 mm          |
| Family construction form  | free cable end |

**Commercial data**

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27279218      |
| ECLASS-6.1            | 27279218      |
| ECLASS-7.0            | 27279218      |
| ECLASS-8.0            | 27279218      |
| ECLASS-9.0            | 27060311      |
| ECLASS-10.1           | 27060311      |
| ECLASS-11.1           | 27060311      |
| ECLASS-12.0           | 27060311      |
| ETIM-5.0              | EC001855      |
| customs tariff number | 85444290      |
| GTIN                  | 4065909072448 |
| Pakke-enhed           | 1             |

**Electrical data | Supply**

|                                    |       |
|------------------------------------|-------|
| Operating voltage AC max.          | 125 V |
| Operating voltage DC max.          | 125 V |
| Operating voltage AC (UL-listed)   | 30 V  |
| Operating voltage DC (UL-listed)   | 30 V  |
| Current operating per contact max. | 4 A   |

**Installation | Connection**

|                           |       |
|---------------------------|-------|
| Stripping length (jacket) | 20 mm |
|---------------------------|-------|

**Device protection | Electrical**

|                                        |                   |
|----------------------------------------|-------------------|
| Additional condition protection degree | inserted, screwed |
| Pollution Degree                       | 3                 |
| Rated surge voltage                    | 1,5 kV            |
| Material group (IEC 60664-1)           | I                 |

**Mechanical data | Material data**

|                  |                   |
|------------------|-------------------|
| Coating locking  | safe-cover coated |
| Material housing | PUR               |
| Locking material | Zinc die-casting  |

**Mechanical data | Mounting data**

|                 |                                       |
|-----------------|---------------------------------------|
| Mounting method | inserted, screwed, Shaking protection |
|-----------------|---------------------------------------|

**Environmental characteristics | Climatic**

|                                        |                            |
|----------------------------------------|----------------------------|
| Operating temperature min.             | -25 °C                     |
| Operating temperature max.             | 85 °C                      |
| Additional condition temperature range | depending on cable quality |

**Important installation notes**

|                        |                                                                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note on strain relief  | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.                                                   |
| Note on bending radius | <b>Attention:</b> Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |

| Conformity                                        |                                                                                                       |
|---------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Product standard                                  | DIN EN 61076-2-101 (M12)                                                                              |
| Installation   Cable                              |                                                                                                       |
| Cable identification                              | 127                                                                                                   |
| Cable Type                                        | 5                                                                                                     |
| Jacket Color                                      | yellow                                                                                                |
| Type of Certificate                               | cURus                                                                                                 |
| Approvals                                         | cURus (AWM-Style 20549/10493), CE compliant, VASS 6 compliant, according to MgU-I-B09-41 (March 2021) |
| Amount stranding                                  | 1                                                                                                     |
| Stranding                                         | 5 wires around Core filler twisted                                                                    |
| Filler                                            | yes                                                                                                   |
| wire arrangement                                  | brown, black, blue, white, gray                                                                       |
| Cable weight                                      | 49,5 g/m                                                                                              |
| Material jacket                                   | PUR                                                                                                   |
| Shore hardness jacket                             | 54 ± 5 Shore D                                                                                        |
| Freedom from ingredients (jacket)                 | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                        |
| Outer-diameter (jacket)                           | 5,2 mm                                                                                                |
| Tolerance outer diameter (sheath)                 | ± 5 %                                                                                                 |
| Material wire insulation                          | PP                                                                                                    |
| Amount wires                                      | 5                                                                                                     |
| Outer diameter insulation                         | 1,25 mm                                                                                               |
| Outer diameter tolerance core insulation          | ± 5 %                                                                                                 |
| Shore hardness wire insulation                    | 73 ± 5 Shore D                                                                                        |
| Ingredient freeness wire insulation               | lead-free, cadmium-free, CFC-free, halogen-free, silicone-free                                        |
| Amount strands (wire)                             | 42                                                                                                    |
| Diameter of single wires                          | 0,1 mm                                                                                                |
| Conductor crosssection (wire)                     | 0,34 mm <sup>2</sup>                                                                                  |
| Material conductor wire                           | Stranded copper wire, bare                                                                            |
| Conductor type (wire)                             | strand class 6                                                                                        |
| Nominal voltage AC max.                           | 300 V                                                                                                 |
| Current load capacity (standard)                  | to DIN VDE 0298-4                                                                                     |
| Current load capacity min. wire                   | 4,5 A                                                                                                 |
| Electrical resistance line constant wire          | 60 Ω/km @ 20 °C                                                                                       |
| AC withstand voltage (wire - wire)                | 2,5 kV @ 60 s                                                                                         |
| Power frequency withstand voltage (wire - jacket) | 2,5 kV @ 60 s                                                                                         |
| Min. operating temperature (static)               | -40 °C                                                                                                |
| Max. operating temperature (fixed)                | 80 °C / 90 °C @ 10000 h Operation                                                                     |
| Operating temperature min. (dynamic)              | -25 °C                                                                                                |
| Operating temperature max. (dynamic)              | 80 °C / 90 °C @ 10000 h Operation                                                                     |
| Flame resistance                                  | IEC 60332-2-2   UL 1581 § 1090   UL 1581 § 1100 FT2                                                   |
| chemical resistance                               | Good, application-related testing                                                                     |
| Gasoline resistance                               | Good, application-related testing                                                                     |
| Oil resistance                                    | DIN EN 60811-404   Good, application-related testing                                                  |
| Bending radius (fixed)                            | 5 x Outer diameter                                                                                    |
| Bending radius (dynamic)                          | 10 x Outer diameter                                                                                   |
| No. of bending cycles (C-track)                   | 10 Mio. @ 25 °C                                                                                       |
| Traversing distance (C-track)                     | 5 m @ 25 °C   horizontal                                                                              |
| Travel speed (C-track)                            | 3,3 m/s @ 25 °C                                                                                       |
| No. of torsion cycles                             | 1 Mio.                                                                                                |
| Torsion stress                                    | ± 360 °/m                                                                                             |
| Torsion speed                                     | 35 cycles/min                                                                                         |