MURR ELEKTRONIK
stay connected

B10 Bulkhead mounted h., IP65

Single locking lever m.

B10
Bulkhead mounted housing
Single locking lever
IP65
Technical data will be only guaranteed with Murrelektronik components.

Link til artikel

Billede



Produktet kan afvige fra billedet

Commercial data	
ECLASS-6.0	27143424
ECLASS-6.1	27261203
ECLASS-7.0	27440202
ECLASS-8.0	27440202
ECLASS-9.0	27440202
ECLASS-10.1	27440202
ECLASS-11.1	27440202
ECLASS-12.0	27440202
ETIM-5.0	EC000437
customs tariff number	85389099
GTIN	4048879644952
Pakke-enhed	1
Installation | Connection	
Mating cycles min.	500
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP65
Additional condition protection degree	inserted, locked, with screw connection
Mechanical data	
Housing type	Bulkhead mounted housing
Mechanical data | Material data	
Coating housing	powder-coated
Coating locking	verzinkt
Material gasket	NBR

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 09.05.2024

Material housing	Aluminum die casting
Locking material	Steel
Mechanical data | Mounting data	
Size	B10
Height	28,5 mm
Width	43 mm
Depth	93 mm
Looking techniques	Single locking lever
Environmental characteristics | Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	100 °C
Climatic category (EN IEC 60068-1)	40/100/21

Oplysningerne i dette datablad er udarbejdet med størst mulig omhu.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 09.05.2024