


B24 frame (female) for 6 modules

a...f


B24  
Frame  
Female  
for 6 modules  
Technical data will be only guaranteed with Murrelektronik components.

Link til artikel

Billede



Produktet kan afvige fra billedet



Commercial data

|                       |               |
|-----------------------|---------------|
| ECLASS-6.0            | 27143424      |
| ECLASS-6.1            | 27261209      |
| ECLASS-7.0            | 27440206      |
| ECLASS-8.0            | 27440206      |
| ECLASS-9.0            | 27440206      |
| ECLASS-10.1           | 27440206      |
| ECLASS-11.1           | 27440206      |
| ECLASS-12.0           | 27440206      |
| ETIM-5.0              | EC002312      |
| customs tariff number | 85389099      |
| GTIN                  | 4048879641814 |
| Pakke-enhed           | 1             |

Installation

|                               |       |
|-------------------------------|-------|
| Connection cross section min. | 1 mm² |
| Connection cross section max. | 6 mm² |
| AWG number min.               | 18    |
| AWG number max.               | 10    |

Installation | Connection

|                                      |                    |
|--------------------------------------|--------------------|
| Connection                           | Screw terminals SK |
| Insertion cycles safety element min. | 20                 |
| Mating cycles min.                   | 500                |

Installation | Pin assignment

|              |        |
|--------------|--------|
| No. of poles | 2 + PE |
|--------------|--------|

**Mechanical data**

|                                     |        |
|-------------------------------------|--------|
| Holding force modules (insert) min. | 300 N  |
| Holding force modules (pull) min.   | 600 N  |
| Holding force PE contact            | 250 N  |
| Frame type                          | female |
| Pulling force max.                  | 60 N   |

**Mechanical data | Material data**

|                             |                  |
|-----------------------------|------------------|
| Coating housing             | nickel plated    |
| Coating contact             | nickel plated    |
| Combustibility class (UL94) | V-0              |
| Material housing            | Zinc die-casting |
| Material contact            | Brass            |
| Material safety element     | PC GF            |

**Mechanical data | Mounting data**

|                        |          |
|------------------------|----------|
| Number of module slots | 6        |
| Size                   | B24      |
| Height                 | 36,5 mm  |
| Width                  | 34,4 mm  |
| Depth                  | 111,2 mm |

**Environmental characteristics | Climatic**

|                                    |           |
|------------------------------------|-----------|
| Operating temperature min.         | -40 °C    |
| Operating temperature max.         | 125 °C    |
| Climatic category (EN IEC 60068-1) | 40/125/10 |