

Male contact carriers 4-pole

Contact carrier
Male
4-pole
Technical data will be only guaranteed with Murrelektronik components.

Link til artikel

Billede



Produktet kan afvige fra billedet

Commercial data	
ECLASS-6.0	27143424
ECLASS-6.1	27261205
ECLASS-7.0	27440205
ECLASS-8.0	27440205
ECLASS-9.0	27440223
ECLASS-10.1	27440223
ECLASS-11.1	27440223
ECLASS-12.0	27440223
ETIM-5.0	EC000438
customs tariff number	85389099
GTIN	4048879649445
Pakke-enhed	1
Electrical data Supply	
Operating voltage AC	50 V
Operating voltage DC	50 V
Operating current	10 A
Industrial communication	
Data transmission rate max.	1000 MBit/s
Installation	
Connection cross section min.	0,14 mm²
Connection cross section max.	2,5 mm²
AWG number min.	26
AWG number max.	13
Installation Connection	
Wire insulation diameter min.	9,5 mm
Connection	Crimp

Gender	male
Mating cycles min.	500
Installation Pin assignment	
No. of poles	4
Device protection Electrical	
Pollution Degree	3
Rated surge voltage	0,8 kV
Insulation resistance min.	100 MΩ
Overvoltage category (EN 60664-1)	I
Overvoltage category (EN 60950-1)	III
Mechanical data Material data	
Combustibility class (UL94)	V-0
Material housing	PA
Mechanical data Mounting data	
Height	20,3 mm
Width	16,7 mm
Depth	46 mm
Environmental characteristics Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	100 °C
Climatic category (EN IEC 60068-1)	40/100/10