



CAP BIG WITH PLUG. SCREW TERM. 21-POLE

For use with 4-,6-,8-way d-box M12 5-pole

Cap for 4-, 6-, and 8-way distribution box, 5-pole  
Screw plug-in terminals  
Plastic housings with good resistance against chemicals and oils.  
The resistance to aggressive media should be individually tested for your application. Further details on request.

[Link til artikel](#)

Billede



Produktet kan afvige fra billedet



| Commercial data |          |
|-----------------|----------|
| ECLASS-6.0      | 27143423 |
| ECLASS-6.1      | 27279219 |
| ECLASS-7.0      | 27279219 |
| ECLASS-8.0      | 27279219 |
| ECLASS-9.0      | 27440108 |
| ECLASS-10.1     | 27440111 |

|                                                 |                         |
|-------------------------------------------------|-------------------------|
| ECLASS-11.1                                     | 27440111                |
| ECLASS-12.0                                     | 27440111                |
| ETIM-5.0                                        | EC002585                |
| customs tariff number                           | 85369010                |
| GTIN                                            | 4048879300056           |
| Pakke-enhed                                     | 1                       |
| <b>Electrical data   Supply</b>                 |                         |
| Total current max.                              | 8 A                     |
| <b>Installation</b>                             |                         |
| Connection cross section max.                   | 1,5 mm <sup>2</sup>     |
| AWG number max.                                 | 16                      |
| <b>Installation   Connection</b>                |                         |
| Connection                                      | Screw plug-in terminals |
| <b>Device protection   Media</b>                |                         |
| Flame resistance                                | flame retardant         |
| <b>Mechanical data   Material data</b>          |                         |
| Material housing                                | Plastic                 |
| <b>Environmental characteristics   Climatic</b> |                         |
| Operating temperature min.                      | -20 °C                  |
| Operating temperature max.                      | 80 °C                   |
| <b>Connection type 1</b>                        |                         |
| Family construction form                        | Cap                     |
| No. of poles                                    | 21                      |